

VERTICAL & HORIZONTAL SCISSOR LIFTS 800-4000 kg

Tables for high lifts and long goods. Table should be fixed into floor with bolted joints. Lifting height up to 4210 mm. Maintenance free pivot bushings. Large safety clearance between the scissors to avoid injuries. Lift cylinder with internal drainage. Safety valve to ensure safety in case of a hose burst. Low-noise power pack with built-in overload valve. Safety switch in top position. Moveable limit switch for adjusting full raised stop. 4 end-stops, incl. 4 loops which can be used e.g. when lifting total lift table into a pit. Low-noise power pack with built in overload valve. Cable for 3-phase connection 380V/16 Ah. Approves to EN1570-1.



MJ-Q801



HD1000



LV4000

TECHNICAL INFORMATION

Art.no	HD1000	HD2000	HT1000	MJ-Q801	LV2000	LV4000
Type	Double scissor	Double scissor	Triple scissor	Four scissor	Horizontal double scissor	Horizontal double scissor
Capacity (kg)	1000	2000	1000	800	2000	4000
Stroke length (mm)	1475	1420	2030	3504	795	770
Tabel area (LxW) (mm)	1300x820	1300x850	1700x1000	1700x1000	2500x820	2500x850
Base frame size (mm)	1240x640	1220x785	1600x1000	1606x1010	2460x640	2450x785
Lifting height, min-max (mm)	305-1780	360-1780	470-3000	706-4210	205-1000	230-1000
Lifting time to max height (s)	35-45	35-45	35-45	70-80	40-45	30-40
Lifting motor	380V/50HZ 2,2 kW	380V/50HZ 2,2 kW	380V/50HZ 2,2 kW	380V/50HZ 2,2 kW	380V/50HZ 1,1 kW	380V/50HZ 1,1 kW
Weight (kg)	210	295	450	858	265	360
Price						