

FORESTRY CHAINS






OFA forestry chains meet the demands of working in tough logging environments in a variety of ways. They significantly improve traction, thereby reducing fuel consumption and increasing productivity. The chains protect the sides and treads of expensive tires from stones, stumps and branches.

OFA has the industry's widest range of tire chain models with different sizes and patterns. Thanks to

the modern manufacturing, comprehensive central warehouse and global dealer network, OFA products are always available wherever professional loggers need them.

The world's best-selling forestry chain OFA Matti W is the most popular chain for all forestry machine applications.

Which chain for which purpose?

												
	Tractor	Forest Tractor	S Small	M Medium	L Large	S Small	M Medium	L Large	S Small	M Medium	L Large	Scarifier
Tapio 11	•••	•	•									
Tapio 11 HD	•••	••	••			•			•			
Twist 11		•••	•••	••		••			•••			
Tapio 13			••	•		•	•		••	•		
Twist 13						•••	••		•••	••	•	
Craftec+ 13			•••	••		•••	••		•••	••	•	
Protec 13			•••			•••	••		•••	•••		
Matti W 13				••		•••	••	•	•••	•••	••	
Twist 16 1D			•••	••								
Craftec+ 16				•••		•••	•••	••		•••	••	
Craftec 16				•••		•••	•••	••		•••	•••	
Protec 16							•••	••		•••	•••	
Paragon 16							•••	•••		•••	•••	••
Matti W 16				•••	••		•••	•••		•••	•••	••
Matti W 19					•••			•••			•••	•••

Matti W 16



ML



ML



ML



UPDATE
2015

Matti W 16 is universal chain for all kind of forest machines. It has 2T, 3T and 3ST tread patterns. Most of the chain dimensions have a tensioning chain for easier tightening. All Matti W 16 chains have 19 mm stud as standard that provides long life time.

Technical specifications

Main tread chain	diam. 16 mm
Stud	diam. 19 mm
Side chain	diam. 13 mm

Matti W 16 3T



Technical improvements to prevent links from turning around:



Bigger
19 mm studs



Mechanical
resistance



Squeezed
links



Matti W 16 2T					Matti W 16 3T			Matti W 16 3ST		
Width	Rim	OFA code	Weight kg/pair	Tension chain	OFA code	Weight kg/pair	Note	OFA code	Weight kg/pair	Tension chain
700/45	22.5"	OL91577022	364	TC						
710/40		OL91577022	364	TC						
18.00	24"	OL91571825	475							
650/45	24.5"	OL91576524	366	TC						
710/40		OL91577124	368	TC	OL91587124	421	TC			
18.00	25"	OL91571825	475							
20.5		OL91572025	404							
22/65		OL91572225	378							
23.5		OL91572325	453							
25/65		OL91572525	442							
26.5		OL91572624	565	TC						
		OL91572625	546							
29.5 L5		OL91572925	625		OL91582925	755				
620/65		OL91572525	442							
23.1	26"	OL91572327	470	TC	OL91582325	556	TC			
		OL91572326	451		OL91582326	540				
28.1		OL91572825	530	TC	OL91582826	628				
		OL91572826	514							
28L		OL91572825	530	TC	OL91582826	628				
		OL91572826	514							
66x43.00					OL91586626	731				
67x34.00					OL91586726	720				
600/55	26.5"	OL91576025	390	TC	OL91586025	464	TC	OL91686026	511	
		OL91576026	377		OL91586026	449				
650/65		OL91576525	457	TC	OL91586526	523				
		OL91576526	441							
700/50		OL91577025	430	TC	OL91587025	480	TC	OL91687026	575	
710/45		OL91577025	430	TC	OL91587025	480	TC			
750/55					OL91587826	565				
780/55					OL91587826	565		OL91687526	635	
800/40	28.5"	OL91578025	446	TC	OL91588025	514	TC			
780/50	29"				OL91587828	556		OL91682928	991	
33.25		OL91573328	716	TC						
775/65					OL91587729	670				
800/65 L3					OL91588029	721				
600/60	30.5"	OL91576030	425		OL91586030	507				
620/55		OL91576030	425							
700/50		OL91577030	445							
800/45					OL91588030	567				
24.5	32"	OL91572334	525		OL91582334	650				
30.5					OL91583033	719	TC	OL91683032	830	
					OL91583032	699				
73x44.00					OL91587332	823				
35/65	33"				OL91583533	851				
18.4	34"	OL91571835	475	TC						
		OL91571834	455							
23.1		OL91572334	525		OL91582334	650		OL91682334	767	
600/65		OL91576033	494	TC	OL91586034	568		OL91686034	669	
		OL91576034	475							
700/55		OL91577033	516	TC	OL91587033	631	TC	OL91687034	698	
		OL91577034	495		OL91587034	611				
700/70					OL91587036	718	TC	OL91687035	828	
					OL91587035	695				
710/55		OL91577033	516	TC	OL91587033	631	TC			
		OL91577034	495		OL91587034	611				
750/65					OL91583033	719	TC			
					OL91583032	699				
600/65	38"	OL91576038	502							