

## STATIC LIFT TABLES | 1000-4000 kg

Maintenance free pivot bushings. Large safety clearance between the scissors to avoid injuries. Lift cylinder with internal drainage. Safety valve to ensure safety in case of a hose burst. Moveable limit switch for adjusting full raised stop. 4 end-stops, incl. 4 loops which can be used e.g. when lifting total lift table into a pit. Low-noise power pack with built-in overload valve. Cable for 3-phase 380V/16Ah. \* Approves to EN1570-1.



HW1001

HW-ST (1000 kg)  
HW-SV (2000 kg)



Pallet truck stand

Capacity 1000 and 2000 kg. By using the pallet truck stand the user gets a good mobility. Fits HW1001/1002/2001/2002 and HD1000.



1 or 2 cylinders = 1000 or 2000/4000 kg.



Low-noise power pack equip-ped with built-in overload valve and flow compensated valve for controlled lowering speed.



The upper platform has a safety frame that covers all four sides. There are double switches for lowering safety of the platform.



Mechanic stop enables safe maintenance.



HW500L

## STATIC LIFT TABLE | 500 kg

Maintenance free pivot bushings. Large safety clearance between the scissors to avoid injuries. Lift cylinder with internal drainage. Safety valve to ensure safety in case of a hose burst. Low-noise power pack with built in overload valve. Cable for 3-phase 380V/16Ah. \* Approves to EN1570-1.

### TECHNICAL INFORMATION

Art.no	HW500L	HW1001	HW1002	HW1004	HW1005	HW1006	HW2001	HW2002	HW2005	HW4002
Type	Single scissor	Single scissor	Single scissor	Single scissor	Single scissor	Single scissor	Single scissor	Single scissor	Single scissor	Single scissor
Capacity (kg)	500	1000	1000	1000	1000	1000	2000	2000	2000	4000
Stroke length (mm)	-	785	785	1060	1060	1060	770	770	1050	810
Lifting height, min-max (mm)	200-1000	205-990	205-990	240-1300	240-1300	240-1300	230-1000	230-1000	250-1300	240-1050
Lifting time to max height (s)	20-25	20-25	20-25	20-25	30-35	30-35	20-25	20-25	25-35	30-40
Table area (LxW) (mm)	2000x800	1300x820	1600x1000	1700x1000	2000x850	2000x1000	1300x850	1600x1000	2000x850	2000x1200
Base frame size (mm)	1615x680	1240x640	1240x640	1580x640	1580x640	1580x640	1220x785	1220x785	1600x785	1600x900
Lifting motor	380V/50HZ 1,1Kw	380V/50HZ 1,1 Kw	380V/50HZ 1,1 Kw	380V/50HZ 1,1 Kw	380V/50HZ 1,1 Kw	380V/50HZ 1,1 Kw	380V/50HZ 2,2 Kw	380V/50HZ 2,2 Kw	380V/50HZ 1,5 Kw	380V/50HZ 2,2 Kw
Weight (kg)	193	160	186	186	212	223	235	268	300	405
Price										

\*Option: 3 phase 230V/50HZ.