

FORESTRY CHAINS







OFA forestry chains meet the demands of working in tough logging environments in a variety of ways. They significantly improve traction, thereby reducing fuel consumption and increasing productivity. The chains protect the sides and treads of expensive tires from stones, stumps and branches.

OFA has the industry's widest range of tire chain models with different sizes and patterns. Thanks to

the modern manufacturing, comprehensive central warehouse and global dealer network, OFA products are always available wherever professional loggers need them.

The world's best-selling forestry chain OFA Matti W is the most popular chain for all forestry machine applications.

Which chain for which purpose?

															
	Tractor	Forest Tractor	S Small	M Medium	L Large	S Small	M Medium	L Large	S Small	M Medium	L Large	Scarifier			
Tapio 11	•••	•	•												
Tapio 11 HD	•••	••	••			•					•				
Twist 11		•••	•••	••		••					•••				
Tapio 13			••	•		•	•				••	•			
Twist 13						•••	••				•••	••	•		
Craftec+ 13			•••	••		•••	••				•••	••	•		
Protec 13						•••	••				•••	•••			
Matti W 13				••		•••	••	•			•••	•••	••		
Twist 16 1D			•••	••											
Craftec+ 16				•••		•••	•••	••			•••	••			
Craftec 16				•••		•••	•••	••			•••	•••	•••		
Protec 16							•••	••			•••	•••	•••		
Paragon 16							•••	•••			•••	•••	•••	••	
Matti W 16				•••	••		•••	•••			•••	•••	•••	••	
Matti W 19					•••			•••			•••	•••	•••	•••	

Twist 16 1D



Twist 16 1D is designed for skidders and working machines.

1-diamond pattern with 16 mm twisted chain provides excellent grip and good self-cleaning.

Width	Rim	OFA code	Weight kg/pair	Tension chain
18.4	26"	OL93598630	294	
23.1		OL93598326	337	
16.9	30"	OL93598630	294	
24.5	32"	OL93598432	417	
18.4	34"	OL93598326	337	
23.1		OL93598432	417	



Twist 16 1D

Technical specifications

Tread chain	diam. 16 mm
Stud	diam. 16 mm
Side chain	diam. 13 mm

Protec



Less tight triple diamond pattern with additional protection for the tire sides against rocks and stumps.

Good self-cleaning. Tension chain as standard. Protec is available in 13 mm and 16 mm chain links.

Technical specifications

Tread chain	diam. 13 mm, 16 mm
Stud	diam. 14 mm, 19 mm
Side chain	diam. 11 mm, 13 mm



UPDATE 2015



Protec 13
Protec 16

Technical improvements to prevent links from turning around:



Bigger
19 mm studs



Mechanical
resistance



Squeezed
links

Protec 13

Protec 16

Protec F16

Width	Rim	OFA code	Weight kg/pair	Tension chain	OFA code	Weight kg/pair	Tension chain	OFA code	Weight kg/pair	Tension chain
700/45	22.5"	OL91197022	276	TC						
710/40	24.5"	OL91197024	298	TC						
600/55	26.5"				OL9148602619	394	TC			
700/50		OL91197026	332	TC	OL9148702419	463	TC	OL81487024	511	TC
710/45					OL9148702419	463	TC	OL81487024	511	TC
750/55					OL9148752619	515	TC	OL81487526	571	TC
700/55	34"				OL9148703319	571	TC	OL81487033	631	TC
710/55					OL9148703319	571	TC	OL81487033	631	TC
700/70					OL9148773419	668	TC	OL81487734	677	TC
710/70					OL9148773419	668	TC	OL81487734	677	TC